



## TECHNICAL SPECIFICATIONS

DESIGNERS : JOUBERT / NIVELT /

LENGHT OVERALL	10.95 M
BEAM	3.55 M
DRAFT	2.10 M
DISPLACEMENT	4450 KG
BALLAST	1990 KG
MAINSAIL	38 M <sup>2</sup>
GENOA	29.5 M <sup>2</sup>
SYMETRIQUE SPI	82 M <sup>2</sup>
SPI ASYMETRIQUE	95 M <sup>2</sup>
P	13.73 M
E	4.59 M
J	4.10 M
FL	MAX 14 M
LP	MAX 4.28 M
STL (POLE)	4.4 m
STL (BOWSPRIT)	5.48 M
AUXILIARY DIESEL	21 HP
CE APPROUVAL	A, 6 PERSONS
	B, 8 PERSONS
	C, 10 PERSONS

### CONSTRUCTION

WHITE HULL PVC SANDWICH RESIN INFUSION SYSTEM  
 WHITE DECK PVC SANDWICH RESIN TRANSFER MOULDING  
 WHITE INTERIOR MOULDING  
 LEAD KEEL  
 RUDDER POLYESTER WITH STAINLESS SOLID STOCK ON SELF ALIGNING BEARINGS

### DECK HARDWARE

BALCON AVANT INOX STAINLESS STEEL PULPIT  
 ANCHOR CHAIN WELL IN BOW DECKING  
 8 STANCHIONS REINFORCED WITH TWO WIRE LINES  
 STAINLESS STEEL PUSH PIT

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE OR OBLIGATION*

**A35 SPECIFICATIONS - [www.bachyachting.nl](http://www.bachyachting.nl)**

4 ALUMINIUM MOORING CLEATS  
RONSTAN / FREDERICKSEN FITTING  
2 GENOA TRACKS  
1 MAINSAIL TRACK  
2 PRIMARIES WINCHES LEWMAR 48 AST  
2 HALYARDS WINCHES LEWMAR 40 AST  
2 MAINSHEET WINCHES LEWMAR 40 AST  
6 SPINLOCK DECKSTOPPERS  
1 COMPASS  
CARBON TILLER WITH TELESCOPIC STICK  
GAS BOTTLE STORAGE  
STORAGE COMPARTMENT IN THE COCKPIT

**SPARS AND RIGGING**

TAPERED MAST IN ANODISED ALUMINIUM 2 SETS OF AFT-SWEPT  
SPREADERS STEPPED  
ALUMINIUM BOOM  
DYFORM RIGGING  
ROD KICKER  
HALYARDS

**INTERIOR LAYOUT**

ALL JOINERY WORK IN MOABI MAHAGONY  
WHITE VINYL LINED CELLINGS  
THE CUSHIONS ARE IN BEIGE FABRIC WITH BLUE LINES

**FORWARD BERTH**

LARGE DOUBLE BERTH  
LEWMAR COMPANIONWAY COVER  
2 SPOTLIGHTS

**SALOON**

SETTEE/BERTHS TO STARBOARD AND PORT SIDE  
TABLE WITH DROP LEAFS  
STAINLESS STEEL HANDRAILS  
2 FIXED COACH-ROOF PORT-LIGHTS  
2 SPOTLIGHTS  
LEWMAR HATCH ON THE COACHROOF  
HEADROOM : 1,85 M

**CHART TABLE**

LARGE CHART TABLE FACING FORWARD  
LARGE HINGED INSTRUMENTS PANEL WITH ELECTRICAL PANEL  
NAVIGATOR SEAT WITH LOCKER

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE OR  
OBLIGATION*

**26/11/2007**

**A35 SPECIFICATIONS - [www.bachyachting.nl](http://www.bachyachting.nl)**

**GALLEY**

COOKER WITH 2 BURNERS STOVE ON GIMBALS  
STAINLESS STEEL SINK  
PRESSURISED COLD WATER  
60 L MOULDED ICEBOX  
LOCKERS

**AFT CABIN ON PORT SIDE**

ACCES DOOR TO SALOON  
LOCKERS  
DOUBLE LARGE DOUBLE BERTH  
COCKPIT OPENING PORT-LIGHT  
2 SPOTLIGHTS  
HEADROOM : 1,80 M

**AFT HEAD ON STARBOARD SIDE**

ACCES DOOR TO SALOON  
LOCKERS  
MARINE TOILET  
HOLDING TANK  
STAINLESS STEEL SINK  
PRESSURISED COLD WATER  
OPENING PORT-LIGHT  
SPOTLIGHT  
HEADROOM : 1,80 M

**AFT TECHNICAL STORAGE ON STARBOARD SIDE**

ACCES BY AFT HEAD  
50 L PLASTIC FUEL TANKER  
PRESSURISED WATER SYSTEM  
BATTERY CHARGER ( OPTION )  
WATER HEATER ( OPTION )

**WATER SYSTEM**

ELECTRIC BILGE PUMP  
HAND-OPERATED BILGE PUMP  
100 L WATER TANK  
PRESSURISED WATER YSTEM  
FLUSH VALVES

**ELECTRICITY**

12 VOLTS CIRCUIT  
2 X 70 AH BATTERY WITH SWITCHES

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE OR OBLIGATION*

**26/11/2007**

**A35 SPECIFICATIONS - [www.bachyachting.nl](http://www.bachyachting.nl)**

12 V ELECTRICAL PANEL WITH 12 SWITCHES

**ENGINE EQUIPMENT**

NANNI ENGINE 3.21 SD10 21 CV SAIL DRIVE  
50 L PLASTIC FUEL TANKER  
SOUND INSULATED COMPARTMENT  
2 BLADED FOLDING PROPELLER  
ENGINE PANEL RECESSED IN THE COCKPIT

**OPTIONS**

TITANE STEERING WHEEL 1,60 M  
SPINNAKER FITTING  
SPINNAKER POLE  
CARBON BOWSPRIT  
ELECTRIC WINDLASS  
BATTERY CHARGER  
WATER HEATER  
ICEBOX/FRIDGE

**FURTHER OPTIONS ARE AVAILABLE CONTACT BACH YACHTING**

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE OR OBLIGATION*

**26/11/2007**